

Omega Supreme Plus ULPA Cleanroom Vacuum by Atrix™



VACOMEGASECRU

PRODUCT HIGHLIGHTS

WARRANTY

3 Year Limited

CLASS 100,000, ISO 8 CLEANROOM VACUUM

With ULPA Premotor and HEPA Postmotor Filtration

POWERFUL

1,000 Hour Rated Ametek Advantek II Motor

QUIET

69 Decibels

SAFE

Combination ULPA/HEPA Filtration along with ESD Safety draining damaging static voltages to ground and built-in electronic line filter to minimize EMI/RFI noise emissions

APPLICATIONS

Class 100,000, ISO 8 Cleanrooms, Clean areas, pharmaceutical, medical, electronic



Ultrafine Vacuums Built to Last. Quality Assured.

www.atrinx.com | sales@atrinx.com | 1-800-222-6154 | Burnsville, MN, USA

Omega Supreme Plus ULPA Cleanroom Vac by Atrix™

SPECIFICATIONS

VACOMEGASECRU

DIMENSIONS

Length: 20" (508 mm)
 Width: 6.25" (159 mm)
 Height: 9.25" (235 mm)

WEIGHT 12.3 lbs. (5.58 kg)

HOSE DIAMETER

Inside - 1.00" (25.4 mm)
 Outside - 1.25" (31.75 mm)

POWER

120, 628W

CFM

99 CFM

INCLUDED CONTENTS

- A - Omega Supreme Plus ULPA Cleanroom Vac by Atrix
- B - 31651-120V Detachable Power Cord
- C - 31657- ESD Safe Flexible Gooseneck Tool
- D - 31671- ESD Safe 10' Stretch Hose
- E - OF712UL- ULPA Filter Cartridge
- F - ATIEF- HEPA Filter (postmotor)
- G - 410017- Filter Plug
- H - AVPA011- NON-ESD Utility Nozzle
- I - AVPA016- Adjustable Shoulder Strap

FILTRATION

PREMOTOR

ULPA
 99.999% Efficient at .12 Micron
 1 Gallon Dry
 56 Pleat, 3 Layer
 One Cellulose Layer
 Two Glass Layers

POSTMOTOR

HEPA
 99.97% Efficient at .3 Micron
 4.5"x4"
 40 Pleat, 3 Layer
 One Cellulose Layer
 Two Glass Layers

GENERAL INFORMATION

PACKAGING

Dimensions: L W H
 Inches: 20.25 7.75 10.75
 mm: 514 197 273
 Weight: 13.55 lbs.
 6.15 kg

HS Code


8508.11.0000

UPC

8 38067 00104 9

OPTIONAL ACCESSORIES

Omega HEPA Filter Cartridge
 with Static Dissipative Body -
 OF912HE



16 Foot Stretch Hose
 31681



ESD Safe Round Brush
 31653



A

G

E

H

D

B

I